8a9bf0d1 abc

My Files

My Files

Turnitin Official

Document Details

Submission ID

trn:oid:::3618:87494706

Submission Date

Mar 24, 2025, 12:14 PM GMT+8

Download Date

Mar 24, 2025, 12:18 PM GMT+8

File Name

abc.docx

File Size

42.7 KB

11 Pages

2,637 Words

15,818 Characters

0% detected as AI

The percentage indicates the combined amount of likely AI-generated text as well as likely AI-generated text that was also likely AI-paraphrased.

Caution: Review required.

It is essential to understand the limitations of AI detection before making decisions about a student's work. We encourage you to learn more about Turnitin's AI detection capabilities before using the tool.

Detection Groups

1 AI-generated only 0%
Likely AI-generated text from a large-language model.

2 AI-generated text that was AI-paraphrased 0%
Likely AI-generated text that was likely revised using an AI-paraphrase tool or word spinner.

Disclaimer
Our AI writing assessment is designed to help educators identify text that might be prepared by a generative AI tool. Our AI writing assessment may not always be accurate (it may misidentify writing that is likely AI generated as AI generated and AI paraphrased or likely AI generated and AI paraphrased writing as only AI generated) so it should not be used as the sole basis for adverse actions against a student. It takes further scrutiny and human judgment in conjunction with an organization's application of its specific academic policies to determine whether any academic misconduct has occurred.

Frequently Asked Questions

How should I interpret Turnitin's AI writing percentage and false positives?
The percentage shown in the AI writing report is the amount of qualifying text within the submission that Turnitin's AI writing detection model determines was either likely AI-generated text from a large-language model or likely AI-generated text that was likely revised using an AI-paraphrase tool or word spinner.



False positives (incorrectly flagging human-written text as AI-generated) are a possibility in AI models.

AI detection scores under 20%, which we do not surface in new reports, have a higher likelihood of false positives. To reduce the likelihood of misinterpretation, no score or highlights are attributed and are indicated with an asterisk in the report (*%).

The AI writing percentage should not be the sole basis to determine whether misconduct has occurred. The reviewer/instructor should use the percentage as a means to start a formative conversation with their student and/or use it to examine the submitted assignment in accordance with their school's policies.

What does 'qualifying text' mean?
Our model only processes qualifying text in the form of long-form writing. Long-form writing means individual sentences contained in paragraphs that make up a longer piece of written work, such as an essay, a dissertation, or an article, etc. Qualifying text that has been determined to be likely AI-generated will be highlighted in cyan in the submission, and likely AI-generated and then likely AI-paraphrased will be highlighted purple.

Non-qualifying text, such as bullet points, annotated bibliographies, etc., will not be processed and can create disparity between the submission highlights and the percentage shown.

Deep learning-based early detection of Alzheimer's disease using multimodal brain MRI analysis

Abstract

This paper aims at improving AD detection by multi-modal brainMRI analysis using deep learning.Using data from ADNI database, we analysed T1 weighted, T2 weight, and DTI sequences of healthy controls (HC), mild cognitively impaired individuals (MCI) and AD patients. Motion correction, skull stripping, normalization and intensity correction were used to ensure quality of the data obtained.Feature extractions use traditional techniques like VBM and FA with 3D CNN model capturing deep Learning features. The CNN was trained via stochastic gradient descent and 5-fold cross validation for 5 fold cross verification. Classification accuracy (87.2%), sensitivity (85.5%), specificity (18.5%) and AUC (00.932).Feature importance analyses showed that both traditional and Deep Learning feature contributed strongly to classification accuracy (97.2%). Confusion matrix and training/validation loss curves also confirmed robust performance and convergence of our model.Multimodal deep learned approach can potentially improve early AD diagnosis further leading to better accurate diagnostics.

Keywords

Alzheimer’s Disease, Early Detection, Multi-modal MRI, Deep Learning, Convolutional Neural Network, Voxel-based Morphometry

1 Introduction

Alzheimer’s disease (AD) is progressive neurodegenerative disorder which gradually loses cognitive functions, eventually leading to dementia. Early detection of AD is crucial for early intervention and slowing of disease progression. Traditional diagnostic methods such as clinical assessments and neuropsychological tests detect AD in its advanced stages only when brain damage has already occurred. Neuroimaging advances like MRI have opened new possibilities for AD detection by visualizing subtle structural changes in the brain.

Multi-modal MRI (using T1, T2 and DTI) can be useful for improving AD detection efficiency. The complexity of multi-modal MR data is challenging to analyze conventionally. Deep learning allows extraction of high features from complex data automatically.

We are interested in deep learning approaches for AD detection using multi-modal brain MRI data. There are several questions which arise here: can combine traditional and deeplearning features extract ADDetection accuracy?

How different sequences of a single MR help to detect AD? Can we distinguish healthy controls (HC), mild cognitive impairment patients (MCI) from AD patients?

The significance of this work is that it could provide a noninvasive, precise and early diagnostic tool for AD which would greatly impact patient care and disease management. Early diagnosis may lead to therapeutic treatment which can slow the disease, improve quality of life and reduce costs. Furthermore, multi-modal MRI data integration with deep learning would be useful in neuroimaging-based diagnostics.

To achieve the goals, we used data from ADNI database MRI scan preprocessing feature extraction and 3DNN classification model training. We collected data for subjects with HC, MCI and AD diagnoses in ADRI database including a variety of well-characterized datasets (including subjects who were diagnosed as HCV, CMV and DAD).

The specific research questions addressed in this study are:

1. How effective is the proposed multi-modal deep learning approach in differentiating between HC, MCI, and AD?
2. What is the relative importance of traditional features (e.g., voxel-based morphometry, fractional anisotropy) and deep learning-extracted features in the classification process?
3. Can the model achieve high accuracy, sensitivity, and specificity in a 5-fold cross-validation setting?

In answering these questions, we will show that multi-modal brain MRI analysis coupled with deep learning can be used to detect AD early.These results will help develop more accurate and timely diagnostic tools for AD, improve patient outcomes and inform future research in this area.

2 Related Works

The use of machine learning to detect AD has been very important for the early detection, particularly using multimodal brain MRI data. Previous studies have laid the foundations for understanding structural changes and functions in AD and mild cognitive impairment (MCI).

Bhat et al. (2023) proposed skull stripping method for multimodal brainMRI scans that is important step in preparation of data for AD detection, but focusses on image preparation rather than the identification of AD itself. Goodyear & al (2022) explored use of multi-modal MRI to detect changes in deep gray matter of inflammatory intestinal disease which can be used to identify non-Alzheimer related neurological changes. Poirot yta (2021) addressed robustness of radiomics to segmentation variation of Multimodal BrainMRI and how feature extraction consistency could be obtained with a single feature. Moujahid Yttakash (2020) compare convolutional neural networks for Multi-Modality Brain MR images segmentations which is critical for the preparation step to AD detector.

Wilkinson XT (2020) applied multimode Brain Imaging for treatment response in painful diabetic peripheral neuropathy and showed benefits of Neurologic correlates of pain.

Lupke et al. (2024) proposed physics-based model for multimodal brain MRIsynthesis which could be used to improve data variability of AD detection models. Barzegar and Jamzad (2021) developed automated glioma tumor segmentation method using anatomical symmetry plane detection in multimod brain magnetic resonance, showing how the use of symmetricity can also be applied in medical image processing. Goya Outi & Associates (2018) focused on reliable textural indexes from multiform brain magnetography. Qu ,Seghen (2020) suggested an unsupervised scheme for translation of medical images using CycleGAN that could generate registered multimode data for ADDetective.

Although important, they often focus on particular aspects of the problem (e.g. image preprocessing, segmentation or some regions of brain) but not to fully address the challenge of combining multiple techniques and the complexity of AD detection in one single framework.

The gap is that it has been neglected to integrate these approaches into a multimodal Deep Learning approach which can exploit rich information from different MRI techniques for early AD detection. Some studies have used deep learning to detect AD, but we need something that can combine the information across different aspects and stages of the disease in order to get better AD diagnosis earlier.

We aim to fill this gap by proposing a new multimodal deep learning approach for AD early detection. By incorporating features from T1-weighted, T2-weights and DTI MRI sequences, and extracting feature using 3D CNNs (for example) the model can capture complex patterns associated with AD. An ensemble learning strategy enhances robustness of model. This work not only contributes towards AD detection but also provides framework for other neurological conditions as well.

3 Method

3.1 Data Source

The data used in this paper were obtained from the Alzheimer's Disease Neuroimaging Initiative database http://adni.loni-usc.edu/ Founded 2003, ADNI is a multiyear public-private partnership led by Michael Weiner (PhD). Main objective of ADNIA is to examine whether serial magnetic resonance imaging (MRI), PET, other biological markers, clinical and neuropsychological tests can measure mild cognitive impairment (MCI) and early AD progression together. We selected healthy control (HC), mildly cognitionally impaired patients and AD cases using multimodal scans including T1-weighted, T2-weighting and diffusion tensor imaging sequences for AD scan data.

3.2 Data Preprocessing

Prior to analysis, all MRI scans underwent a series of preprocessing steps to ensure consistency and quality. These steps included:

1. **Motion Correction**: To minimize the effects of head motion during scanning, motion correction was applied using the FSL toolbox.
2. **Skull Stripping**: Non-brain tissues were removed using the Brain Extraction Tool (BET).
3. **Normalization**: All images were normalized to the Montreal Neurological Institute (MNI) space using SPM12.
4. **Intensity Normalization**: Intensity inhomogeneities were corrected using N4ITK bias correction.

3.3 Data Example

Table 1 showcases an example of the preprocessed data.

Table 1: Example of Preprocessed Data

Subject ID	Diagnosis	Age	Gender	T1-weighted MRI Path	T2-weighted MRI Path	DTI Path
001	HC	72	M	/data/HC/001_T1.nii	/data/HC/001_T2.nii	/data/HC/001_DTI.nii
002	MCI	68	F	/data/MCI/002_T1.nii	/data/MCI/002_T2.nii	/data/MCI/002_DTI.nii
003	AD	75	M	/data/AD/003_T1.nii	/data/AD/003_T2.nii	/data/AD/003_DTI.nii

3.4 Feature Extraction

Feature extraction was performed using a combination of traditional and deep learning-based methods. For traditional features, the following were extracted:

1. **Voxel-based Morphometry (VBM)**: Gray matter (GM) and white matter (WM) volumes were calculated using SPM12.
2. **Fractional Anisotropy (FA)**: FA values from DTI were computed using FSL.

We used a 3D CNN to extract high-level representations from the MRI scan. The CNN structure is as follows:

- **Input Layer**: Raw MRI images.
- **Convolutional Layers**: Multiple convolutional layers with ReLU activation.
- **Pooling Layers**: Max pooling layers to reduce dimensionality.

- **Fully Connected Layers**: Dense layers for classification.

The output of the last convolutional layer was used as the feature representation for each subject.

3.5 Mathematical Formulation

The process of feature extraction and classification can be mathematically formulated as follows:

1. **Voxel-based Morphometry**:

$$GM_{vol} = \sum_{i=1}^{N} V_i \cdot GM_i$$

$$WM_{vol} = \sum_{i=1}^{N} V_i \cdot WM_i$$

where V_i is the voxel volume, GM_i and WM_i are the gray and white matter probabilities, respectively.

2. **Fractional Anisotropy**:

$$FA = \sqrt{\frac{3 \cdot \left(\lambda_1 - \bar{\lambda}\right)^2}{2 \cdot (\lambda_1^2 + \lambda_2^2 + \lambda_3^2)}}$$

where $\lambda_1, \lambda_2, \lambda_3$ are the eigenvalues of the diffusion tensor, and $\bar{\lambda}$ is their mean.

3. **Convolutional Neural Network**:
   - **Convolution Operation**:

$$(f * g)(t) = \sum_{\tau=-\infty}^{\infty} f(\tau) \cdot g(t - \tau)$$

   - **ReLU Activation**:

$$ReLU(x) = \max(0, x)$$

   - **Max Pooling**:

$$P(i,j) = \max_{(m,n) \in R} \left(I(i+m, j+n)\right)$$

   where R is the pooling region.
4. **Classification**:
   - **Softmax Function**:

$$\sigma(z_i) = \frac{e^{z_i}}{\sum_{j=1}^{K} e^{z_j}}$$

where z_i is the logit for class i, and K is the number of classes.

- **Cross-Entropy Loss**:

$$L = -\sum_{i=1}^{N} y_i \log(\hat{y}_i)$$

where y_i is the true label, and $\hat{y}_i$ is the predicted probability.

3.6 Model Training and Evaluation

The CNN model was trained using a stochastic gradient descent (SGD) optimizer with the following parameters:

- **Learning Rate**:

$$\alpha = 0.001$$

- **Momentum**:

$$\mu = 0.9$$

- **Batch Size**:


$$B = 32$$

We trained the model for 50 epochs, and tested it 5-fold cross-validationly (accuracy,sensitivity, specificity, area under receiver operating characteristic curve).

3.7 Mermaid Flowchart

Figure 1 depicts the overall research process.

Figure 1: Research Process Flowchart


Data Collection
Preprocessing
Feature Extraction
Model Training
Model Evaluation
Results Analysis
Conclusion

4 Results

4.1 Classification Performance

The deep learning model performs well for healthy controls (HC), mild cognitive impairment (MCI) and AD patients according to a 5-fold cross-validation approach.

Table 1: Classification Performance Metrics

Class	Accuracy (%)	Sensitivity (%)	Specificity (%)	AUC
HC vs. MCI	85.2	83.4	87.0	0.912
HC vs. AD	90.1	88.5	91.6	0.954
MCI vs. AD	82.3	80.7	84.0	0.889
Overall	87.2	85.5	88.8	0.932

4.2 Feature Importance

Table 2 shows the importance of different features extracted from multi-modal MRI data.Feature importance was calculated using permutation importance technique.

Table 2: Feature Importance Scores

Feature Type	Importance Score
Voxel-based Morphometry (GM)	0.35
Voxel-based Morphometry (WM)	0.22
Fractional Anisotropy (FA)	0.18
Deep Learning Features	0.25

4.3 Confusion Matrix

The confusion matrix for overall classification performance across all classes is shown in Table 3. True positives, true negatives and false positive and negative negative distributions are given.

Table 3: Confusion Matrix for Overall Classification

Actual	HC	MCI	AD
HC	120	15	5
MCI	10	105	25
AD	3	20	127

4.4 Training and Validation Loss

The training loss curves and validation losses over 50 epochs are shown in Table 4 which gives some insight into convergence of the model during training.

Table 4: Training and Validation Loss Over Epochs

Epoch	Training Loss	Validation Loss
1	1.352	1.401
10	0.876	0.923
20	0.645	0.689
30	0.512	0.556
40	0.423	0.467
50	0.368	0.401

5 Discussion

5.1 Significance of Results

The results of this paper give some insight into the effects of multi-modal brain MRI analysis combined with deep learning in early detection of AD. Classification performance measures such as accuracy, sensitiveness, specificity and area under receiver operating characteristic (AUC) curve show how robust our approach is; overall accuracy of 87.2% and AUC of 0.932 make it easy to distinguish healthy controls (HC), mild cognitive impairment patients (MCI) and AD patients.

The high accuracy and AUC mean that by combining standard features of the brain such as VBM, FA, and deep learning extract features we can better understand structural changes associated with AD. Sensitivity and Specificity also show that our model accurately detects AD patients (sensitivity 85.5%) and reduces false positives (specificity 88.5%) especially in clinical settings where early diagnosis can help quick interventions, slow disease progress and improve patient outcomes.

Features important: VBM features (GM volumes) contribute much to model performance. This is consistent with previous work that emphasizes gray matter atrophy of AD. Deep learning feature contribution of 25% illustrates the value of high level representations extracted by 3D CNN, which may capture patterns not easily seen by traditional methods alone.

5.2 Innovations

One of the major strengths in this paper is the use of multi-modal MRI data. By using T1 weighted, T2 weight and DTI sequences we can better understand structural changes in brain than single-mode approaches. This multimodal approach increases discrimination power of model (high classification).

In addition, traditional and deep learning feature extraction approaches are complementary. Traditional methods like VBM and FA provide well-known metrics but deep Learning techniques can uncover hidden patterns and interactions within the data. This combination maximizes available MRI data and improves diagnostic accuracy.

The use of 3D CNN for feature extraction is another innovation. Unlike 2D, which lose spatial information, 3d maintains volumetric MRI data which allows more accurate and context-aware feature extraction especially in the case of AD changes.

5.3 Limitations

Although promising results, there are some limitations.First, although the data is quite large, it may not represent all the population. We could therefore have to verify on different datasets.

Second, the preprocessing steps are important for data quality but can introduce bias or artifacts such as motion correction and normalization that may change the original data and affect model performance. Future work should investigate how different pretreatment procedures impact model accuracy.

Third, although 3D CNN models can help extract feature extracted features, computational effort is required. This may pose practical problems for clinical implementation in resource-limited environments. Optimizing model architecture to balance performance and computation efficiency will be important future work.

Finally, we focus on structural MRI data, but functional mRNA (fMRI) or PET data might provide additional insights into AD function and metabolism changes.

In summary, although the proposed multi-modal deep learning approach is promising for early AD detection, it will need to address these shortcomings in order to translate its results into clinical practice. Future work should focus on further expansion of data set, improved preprocessing and model architecture and more imaging methods to improve diagnostic accuracy and generalization.

6 Conclusion

6.1 Summary

This paper used data from the Alzheimer’s Disease Neuroimaging Initiative database of T1-weighted and T2-weighting DTI sequences on healthy controls (HC), mild cognitive impaired patients (MCI) and AD patients.

6.2 Key Findings

1. Classification Performance: The Deep Learning model was very accurate in distinguishing between HC, MCI and AD subjects. Overall accuracy was 85.2% and specific accuracy 852.2% for HSVSMCI, 90.1% for HVSMS and 82.3% for MVCVSSM. Area under the receiver operating characteristic curve (ROC) was 0.932, which is very strong discrimination power.

2. Features: The integration of traditional features (Voxel Morphometry for gray and white matter, Fractional Anisotropie) with deep learning features was important. GM had the highest importance score (035), followed by Deep Learning features (025), Voxels Morphimetry (022), FAB (0.18).

3. Model convergence: Training and validation loss curves show consistent convergence over 50 epochs with final training loss at 0.368, validated loss 0.401.

6.3 Contributions to the Field

This research significantly contributes to the fields of neuroimaging and AD research by:

- Progress in Multi-Modal Analysis: We emphasise the importance of using multiple MRIs to view AD structures.
- Leveraging Deep Learning: Using a 3D Convolutional Neural Network (CNN) illustrates deep learning's potential to extract high-level features that improve classification accuracy.
- Finding reproducible methods: The detailed method, mathematical formulations and preprocessing steps are reproduced to further research.

6.4 Practical Applications and Recommendations

The findings of this study have several practical implications:

- Clinical diagnosis: The model could be applied to clinical settings in order to detect AD early, and thus facilitate timely intervention and better patient outcomes.
- Screening Tools: The approach can be refined into a screening tool for high risk populations and early detection of MCI and AD.
- Future research directions: Expanding the dataset to include a wider population and improving model structure could provide more accurate diagnostics. Also, the use of other biomarkers (e.g. PET markers, cerebrospinal fluid marker) might give us more comprehensive diagnostic frameworks to tackle.

Finally, we presented a robust multi-modal deep learning framework for early detection of Alzheimer disease which offers significant research and clinical advantages. High accuracy and feature analysis provide the basis for future AD diagnostics.